

GALAXY® GX2 Automated Test System

- Simple and intelligent testing and calibration of MSA ALTAIR and ALTAIR PRO Single-Gas Detectors, as well as ALTAIR 4X/4XR and ALTAIR 5X/5X PID Multigas Detectors
- Performs as either stand-alone unit or integrated portable detector management system
- Color touchscreen for ease of setup and viewing; no touch operation is needed for calibration or bump test
- RFID automated calibration gas setup, status alerts and traceability
- Global platform—many language options
- Significant cost of ownership reduction when used with MSA XCell Sensors
- Simultaneous testing of up to 10 gas detectors
- Securely configure gas detectors at the touch of a button
- MSA ALTAIR Multigas Detectors are always ready for use



GALAXY GX2 SYSTEM TEST STAND/ 1 VALVE <i>for use with 1 calibration gas cylinder</i>	10128644	ALTAIR / ALTAIR PRO / ALTAIR 2X Detectors, no-charging
	10128630	ALTAIR 4/4X Multigas Detector, charging
	10128642	ALTAIR 4/4X Multigas Detector, no-charging
	10128626	ALTAIR 5/5X Multigas Detector, charging
	10128628	ALTAIR 5/5X Multigas Detector, no-charging
GALAXY GX2 SYSTEM TEST STAND/ 4 VALVE <i>for use with 1–4 calibration gas cylinders</i>	10128643	ALTAIR / ALTAIR PRO / ALTAIR 2X Detectors, no-charging
	10128629	ALTAIR 4/4X Multigas Detector, charging
	10128641	ALTAIR 4/4X Multigas Detector, no-charging
	10128625	ALTAIR 5/5X Multigas Detector, charging
	10128627	ALTAIR 5/5X Multigas Detector, no-charging
CALIBRATION GAS	10048280	Calibration gas cylinder (34L) 1.45% CH ₄ , 15% O ₂ , 60 ppm CO, 20 ppm H ₂ S
	10045035	Calibration gas cylinder (58L) 1.45% CH ₄ , 15% O ₂ , 60 ppm CO, 20 ppm H ₂ S
	10117738	Calibration gas cylinder (58L) 1.45% CH ₄ , 15% O ₂ , 60 ppm CO, 20 ppm H ₂ S, 10 ppm SO ₂
	10098855	Calibration gas cylinder (34L) 1.45% CH ₄ , 15% O ₂ , 60 ppm CO, 20 ppm H ₂ S, 10 ppm SO ₂
	10103262	Calibration gas cylinder (58L) 1.45% CH ₄ , 15% O ₂ , 60 ppm CO, 20 ppm H ₂ S, 2.5% CO ₂
ACCESSORIES	10105756	Electronic cylinder holder
	10125135	Non-electronic cylinder holder
	10127111	4 GB SD card
	10123937	Digital secure USB key
	10125907	End cap
	10127422	ALTAIR 4/4X Detector Multi-unit Charger, NA
	10127427	ALTAIR 5/5X Detector Multi-unit Charger, NA
	10127112	Laminated quick start guide
	10127518	12" (TBR) Ethernet cable for test stand to test stand connection
	10126657	DIN rail clip kit (2 clips & screws per kit)
	10062364	Type Omega DIN Rail 0.5m, perforated, steel, zinc-plated
	10062365	Type Omega DIN Rail 1m, perforated, steel, zinc-plated
	10062366	Type Omega DIN Rail 2m, perforated, steel, zinc-plated
	10082834	USB IR dongle (for use with MSA Link Software)

GALAXY GX2 Automated Test System

ACCESSORIES	10034391	Demand flow regulator (universal)
	710289	Large capacity (<3000 psi) demand regulator
	10124286	NA power supply (1 of 2)
	10127146	NA power cord (2 of 2)
	10126268	Vehicle power adapter
	10127808	Printer - detector or receipt sticker
	10126437	Detector sticker label roll
	10126138	Receipt & sticker label roll
	10145138	Printer ribbon

Galaxy GX2 Assemble-To-Order (ATO) Options

To create your Galaxy GX2 Test System configuration, select the instrument option codes and mark them in the boxes to the right.

A	TEST STAND INSTRUMENT TYPE	Each instrument type has a dedicated GALAXY GX2 System test stand. 10 test stands can be banked together in any combination, allowing for ultimate flexibility.	Test Stand Options ALTAIR/ALTAIR Pro/ALTAIR 2X Detector ALTAIR 4/4X Detector ALTAIR 5/5X Detector	Code A B C	Selection
B	ACTIVE CYLINDER PORTS	Single valve test stands allow for only one calibration cylinder to be used. 2 valves allow for 1-2 calibration cylinders. 4 valves allow for 1-4 calibration cylinders to be accessed.	Calibration Cylinder Options 1 Valve / 1 Cylinder 2 Valves / Up to 2 Cylinders 4 Valves / Up to 4 Cylinders	Code 1 2 4	Selection
C	INSTRUMENT CHARGING	Instrument charging allows for a single instrument to be charged per test stand. Only available on ALTAIR 4/4X and ALTAIR 5/5X Multigas Detector test stands. Choose Yes/1 if you wish to use the "always ready" function of ALTAIR 4X or ALTAIR 5X Detectors.	Test Stand Options No Yes	Code 0 1	Selection
D	SMART CYLINDER HOLDER	Smart cylinder holder provides calibration gas information and gas levels. Information such as part number, gas types, concentrations, expiration date, lot number, and real time pressure levels are automatically set up in the test stand. Smart cylinder holder provides end users with automated, remote warnings as to low or no gas and expired or nearly expired cylinders.	Smart Cylinder Holder Options None 1 Cylinder Holder 2 Cylinder Holders 3 Cylinder Holders 4 Cylinder Holders	Code 0 1 2 3 4	Selection
E	MULTI-UNIT CHARGER	Selection of ALTAIR 4/4X Detector and multi-unit charger provides charging for 1-4 ALTAIR 4/4X Detectors. Selection of ALTAIR 5/5X Detectors and multi-unit charger provides charging for 1-4 ALTAIR 5/5X Detectors.	Multi-unit Charger Options None Multi-unit charger	Code 0 1	Selection
F	POWER CORD	Each test stand (with the exception of Argentina version) comes with 6V power supply. Power cord option then chooses the appropriate power cord by region. None provides power supply and no power cord. Argentina version provides no power supply and no power cord.	Power Cord Options North America Europe United Kingdom Australia Argentina None	Code N E U A R 0	Selection
H	SECURE DIGITAL USB	Allows end user to securely configure instrument set points at GALAXY GX2 System test stand. Must be inserted to process any setting changes to an instrument.	Secure Digital USB Options None 1 Secure Digital USB Key	Code 0 A	Selection

Your Model Part Number

Please transfer your option codes from the Selection boxes above into the appropriate boxes here and contact your Safety Products Distributor to place your order.

Selection A B C D E F H

A-GX2- 0 0