

FIRE

EXTINGUISHER



Carbon Dioxide

- Well suited for corrosive environments
- Super durable polyester powder paint finish with superior corrosion resistance
- Industrial strength aluminum cylinder
- Stainless steel handles, pull pin, retaining chain and hose band
- Chrome plated solid brass valve
- Strong impact resistant horn
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- D.O.T. Approved Cylinder
- U.S.C.G. Approved with bracket listed on label
- Temperature range: -22°F to 120° F (-30°C to 49°C)



Brand	Product Code	Capacity	Chemical	Discharge Time	Range	ULC & ULC Rating
Strike-first	SF-5CO2	5 lbs	CO2	10 seconds	6-12 ft	5B:C
Strike-first	SF-10CO2A	10 lbs	CO2	10 seconds	6-12 ft	10B:C
Strike-first	SF-15CO2	15 lbs	CO2	15 seconds	6-12 ft	10B:C
Strike-first	SF-20CO2	20 lbs	CO2	20 seconds	6-12 ft	10B:C



MEETS OR EXCEEDS:
ANSI/UL 299 & 711



MEETS OR EXCEEDS:
CAN/ULC-S504 & S508



CLASS B

**FLAMMABLE
LIQUIDS
& GASES**



CLASS C

**ELECTRICAL
CONDUCTIVITY**



**5 YEAR
WARRANTY**

